

# ROADX

## RACING RT01



A tread pattern specifically designed for racing, but also DOT approved for street legal use. When reaching higher operating temperatures the softened tread becomes highly viscous to improve grip and meet all competition requirements.



### ▪ Driving Stability

Increased width of the central area and straight rib design ensure driving stability, especially when driving at high speeds.

### ▪ Shoulder Design

The outside of the tire employs a broad lug design which ensures stability and handling while turning.

### ▪ Tread Pattern

Tread pattern grooves are specially angled to prevent damage in the case of emergency braking or skidding.

### ▪ Style

High-end product with unique sidewall design with curved incisions to full reflect a sporty look.

### Inner Tread Elements ▪

Slanted blocks and wide grooves improve tire grip and water drainage.



RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX LOAD	MAX.PRESSURE	UTQG	SIDEWALL
				mm	inch	mm	mm	KG	kPa		
15	195/50R15	82V	--	6.5	6J	201	577	475	300	180/AAA	BSW
17	225/45ZR17	94W	XL	6.5	7 1/2J	225	634	670	340	180/AAA	BSW
18	235/40ZR18	95W	XL	6.5	8 1/2J	241	645	690	340	180/AAA	BSW
18	265/35ZR18	97W	XL	6.5	9 1/2J	271	643	730	340	180/AAA	BSW
18	285/35ZR18	101W	XL	6.7	10J	290	657	825	340	180/AAA	BSW



# SPORT RS

## Benefits and Features

Ideal drifting tyre with special design and components based on competition experiences

Asymmetric tread design with big pattern blocks and special compound provides superior grip ability

Continuous center rib generates better grip in dry conditions and enhances high-speed stability



Sport



Braking



Silica



Asymmetric

Rim Size	15 - 20
Series	30 - 50
Speed Rating	V - W

Rim(Inch)	Size	Service Index	Standard Rim	Section Width (mm)	Overall Diameter (mm)	Max. Load (kg)	Max. Air Pressure (kpa)	UTQG			TT/TL
15"	195/50R15	82V	6.0J	201	577	475	300	240	AA	A	TL
	205/50R15 XL	89V	6.5J	214	587	580	350	240	AA	A	TL
16"	205/45ZR16 XL	87W	7.0J	206	590	545	350	240	AA	A	TL
	225/50R16 XL	96W	7.0J	233	632	710	350	240	AA	A	TL
17"	235/40ZR17	90W	8.5J	241	620	600	300	240	AA	A	TL
	245/40ZR17 XL	95W	8.5J	248	628	690	350	240	AA	A	TL
	215/45ZR17	87W	7.0J	213	626	545	300	240	AA	A	TL
	225/45ZR17 XL	94W	7.5J	225	634	670	350	240	AA	A	TL
	235/45ZR17	94W	8.0J	236	644	670	300	240	AA	A	TL
18"	265/35ZR18 XL	97W	9.5J	271	643	730	350	180/240	AA	A	TL
	285/35ZR18 XL	101W	10.0J	290	657	825	350	180/240	AA	A	TL
	225/40ZR18 XL	92W	8.0J	230	637	630	350	240	AA	A	TL
	235/40ZR18 XL	95W	8.5J	241	645	690	350	180/240	AA	A	TL
19"	275/30ZR19 XL	96W	9.5J	278	649	710	350	240	AA	A	TL
	235/35ZR19 XL	91W	8.5J	241	647	615	350	240	AA	A	TL
	285/35ZR19 XL	103W	10.0J	290	683	875	350	240	AA	A	TL
20"	275/35ZR20 XL	102W	9.5J	278	700	850	350	180/240	AA	A	TL
	285/35ZR20 XL	104W	10.0J	290	708	900	350	180/240	AA	A	TL
	255/40ZR20 XL	101W	9.0J	260	712	825	350	180/240	AA	A	TL